

# Labino® TrAc Pack Standard - White



## POWERFUL | BATTERY OPERATED

MAKES IT BRIGHT

- Labino® TrAc Pack Standard White lamps have a unique *white* luminance, which makes it possible to see things that have not been possible before.
- The Labino® TrAc Pack Standard is a two-part lamp consisting of a light weight luminary unit and a ballast unit (electronics and battery).
- The Labino® TrAc Pack Standard lamp is available in three important distinctions – floodlight, midlight or spotlight – each giving different beams and intensities.
- The Labino® TrAc Pack Standard obtains full power in 5-15 seconds and can be switched on and off, without the need for pre-cooling.
- You can use the lamp outdoors, even in the rain, as the lamp is IP65 certified.
- Labino® TrAc Pack Standard lamps are based on two key components – the Labino DL-35 W Gas Discharge Bulb (MPXL-technology) and the Labino Trigger Ballast (Electronics). The interface technology between these key components creates unbeatable output performance.
- Manufactured in Sweden.



TrAc Pack Standard

## TECHNICAL SPECIFICATION

### Floodlight

Distribution angle: approx. 45°  
Luminous flux: 3 500 lm

### Midlight

Distribution angle: approx. 20°  
Luminous flux: 3 500 lm

### Spotlight

Distribution angle: approx. 3.5°  
Luminous flux: 3 500 lm  
Intensity approx. 250 000 cd at 2500 mm

### Voltage

- Charger: 100, 115, 230 VAC
- Internal Battery: 12/24 VDC
- Input Power: 43 W
- Output Power: 35 W

### Weight

- Luminary Unit: 1.2 kilos (2.6 lbs)
- Battery and Electronic Unit: 4.4 kilos (9.7 lbs)

### Cables

- Between Luminary and Battery/Electronic Unit: 2.3 meters (2.5 yd)

### Battery

- 12 V, 7.2 Ampere, Lead
- Running time: 1.2 hours +/- 5%
- Charging time: 5-8 hours
- First time charge: 8 hours

### Additional Information

- Mechanical Stability (bulb): IEC810
- Service life (bulb): approx. 5 000 hrs
- Start-up time: full power after 5-15 sec
- Material in housing: anodized aluminium, plastics PA6-30
- The housing is via pre milled slots prepared for mounting devices
- S, CE, ETL/cETL approved
- IP65 classified, dust and temporary water jetting proof

DISTRIBUTOR:

Labino AB shall not be held liable for any errors or omissions resulting from the test procedures that were used in validating performance of any Labino AB product nor for unforeseen errors or omissions in digital or printed material.